

# Introducing the Ascom a72



Ascom a72

*Reliable, robust and easy to use, the Ascom a72 is a messaging and alarm unit specially developed for work places where urgent situations require immediate action. Depending on your needs, there are three versions to choose from.*

## Convenient and smart

One of the most prominent features of the Ascom a72 is its size. The unit is large enough to display messages clearly and small enough to be easy to carry. Thanks to a built-in antenna, users won't have to worry about it getting stuck in their clothes. Should the unit get stuck all the same, a clip release function ensures it doesn't break. The unit is also equipped with an ID label for quick identification.

## Reliable messaging

Messages are presented in plain text on a large backlit LCD display, which means they can be read even in the dark. High priority messages can be programmed to be sent to the front of the messaging queue, interrupting any ongoing messages. That way you can be sure important messages reach their destination immediately.

The a72 supports group messaging where the same message can be sent to a group of people simultaneously to save time and ensure accuracy.

With a72 Protector version it's also possible to acknowledge a message so you will know your message has been received. When you're out of reach, the system will notify the person looking for you. The moment you put your unit in the rack charger, the system will be notified that you are absent.

Features	Pager	Alarm	Protector
Vibration function	✓	✓	✓
Availability information/absence	✓	✓	✓
Messaging	✓		✓
Two-way messaging			✓
Acknowledge			✓
Data send and Data with prefix			✓
Push-button alarm		✓	✓
Man-down and No movement alarm		✓	✓
Pull cord alarm		✓	✓
Location with Ascom IR and LF technologies		✓	✓
Acoustic Location Signal (ALS)		✓	✓

## **Help is just a button-push away**

You can pre-program different security alarms for different situations. In an emergency, just press the alarm button. Your position is located with excellent accuracy, and back-up dispatched to your assistance without delay. Thanks to the IR & LF positioning features, the alarm can be used both indoors and outdoors. Select the positioning system that best suits your environment.

## **Automatic alarms**

An alarm is automatically sent if the unit is taken from the user by force or if the user is in a horizontal position or immobile for a pre-defined period of time. A blink, vibration or beep signal will sound before the alarm is sent in case the alarm was triggered accidentally, thereby eliminating false alarms.

## **Intrinsically safe versions**

The Ascom a72 Pager and a72 Protector are also available in EX versions – approved for use in potentially explosive environments.

## **Accessories:**

- Leather case
- Charging rack for 6 unites
- Single charger
- Battery pack charger

## Ascom a72 technical specifications

<p><b>BODY</b>  <b>Dimensions:</b> (l × w × d): 104 × 62 × 36 mm incl. clip  <b>Weight:</b> 123 g incl. battery  <b>Material:</b> PC/ABS, TPE  <b>Color:</b> black  <b>Clip:</b> Hinge-type (standard)</p>	<p><b>ENVIRONMENTAL</b>  <b>Operating temperature:</b> –10°C to +55°C  <b>Storage temperature:</b> b –20°C to +55°C  <b>Enclosure protection:</b> IP64, IEC EN 60529  <b>Immunity to electromagnetic fields:</b> 3 V/m, EN 61000-4-3 Immunity to ESD: 8 kV contact discharge and 16 kV air discharge, EN 61000-4-2  <b>Free fall test:</b> IEC 60068-2-32, procedure 1, dropped 12 times from 1 meter, specification extended to 1.5 meter</p>
<p><b>LANGUAGES</b>  Danish, Dutch, English, Finnish, French, German, Italian, Norwegian, Portuguese, Spanish, Swedish</p>	<p><b>RADIO</b>  <b>Frequency range:</b> 420–475 MHz  <b>Modulation:</b> FSK  <b>Channel spacing:</b> 6.25/10/12.5/25 kHz  <b>Deviation:</b> 2.5 kHz  <b>Antenna:</b> Internal  <b>Sensitivity:</b> 13 dBμV/m  <b>Radiated power:</b> 50 mW ERP (TBD ATEX/UKEX/IECEX)</p>
<p><b>DISPLAY</b>  <b>Display (w × h):</b> 142 × 80 DOT Matrix LCD (35 × 24 mm active area)  <b>Simultaneously showing rows:</b> Depending on font: 6 (small), 5 (medium), 4 (large) Scroll bar indicates that there are additional rows  <b>Max. No. of characters per row:</b> 27–32 (small), 23–28 (medium), 17–22 (large)</p>	<p><b>LOCATION<sup>1</sup> AND ALARM (ALARM AND PROTECTOR VARIANTS ONLY)<sup>2</sup></b>  <b>Location types<sup>1</sup>:</b> Infrared (IR), Low Frequency (LF)  <b>Alarm types<sup>2</sup>:</b> Push button, man-down, no-movement and/or pull-cord</p>
<p><b>BATTERY AND CHARGING</b>  <b>Type:</b> Li-Ion  <b>Charge time:</b> a Approx. 2 hours  <b>Discharge/charge cycles:</b> ≥80% capacity left after 400 full charge/discharge cycles</p>	<p><b>MESSAGING (Pager and Protector versions)</b>  <b>Message length:</b> Up to 128 characters per message  <b>Storage capacity:</b> 20 messages<sup>1</sup></p>

# ascom

### Ascom Holding AG

Zugerstrasse 32  
CH-6340 Baar  
Switzerland  
info@ascom.com  
Phone: + 41 41 544 78 00  
ascom.com

### About Ascom

Our vision is a world where the right information moves people forward. Our mission is to put the right information in the right hands at the right time so that people can make the best possible decisions.

We are a global provider of communication and collaboration solutions for the acute care, long-term care and enterprise sectors. Our solutions are based on intelligent integrations with software and hardware that are open source and compatible with third party solutions. Every single second, our systems generate large amounts of data, which we then turn into useful and actionable information. This helps us to bring data to life for people in the toughest operational environments, ensuring smooth, complete, and efficient workflows.

Ascom is headquartered in Baar (Switzerland), has operating businesses in 19 countries and employs around 1,400 people worldwide. Ascom registered shares (ASCN) are listed on the SIX Swiss Exchange in Zurich.